



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 2210F12F

Cable reel s. 280, without transformer. Number of conductors 2, cable type 2 x 1 - H05 RN-F, cable length 14 + 1 (m). Equipped with both fluorescent lights 11W and supply voltage 12 V DC. Rewinding clutch as standard.

AREAS OF USE

Aeronautics, Agriculture, Automotive, Cleaning, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Shipping and offshore, Railway transport

FEATURES

| | |
|--------------------------------------|---------------------|
| Information | without transformer |
| Protection degree of electrical part | IP44 |
| Environment temperature | -5 ÷ +40 °C |
| Number of conductors | 2 |
| Cable type | 2x1 - H05 RN-F |
| Cable length | 14 + 1 m |
| Cable inlet | 1,2 m |
| Inlet voltage | 12 V DC |
| Lamp power supply voltage | 12 V DC |
| Lamp connection | E27 |
| Max power | 11 W |
| Lamp protection degree | IP65 |
| Light bulb supplied | p/n 728002 |
| Rewinding clutch | yes |
| Lamp | p/n F12 |
| Packing | No. 1 - 0,043 m3 |



OVERALL DIMENSIONS (mm)



Gross weight

6,8 ÷ 8,8 kg