



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 2210F23

Cable reel s. 280, without transformer. Number of conductors 2, cable type 2 x 1 - H05 RN-F, cable length 14 + 1 (m). Equipped with both fluorescent lights 11W and supply voltage 230 V AC 50 Hz

AREAS OF USE

Aeronautics, Agriculture, Automotive, Cleaning, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Shipping and offshore, Railway transport

FEATURES

Information	without transformer
Protection degree of electrical part	IP44
Environment temperature	-5 ÷ +40 °C
Number of conductors	2
Cable type	2x1 - H05 RN-F
Cable length	14 + 1 m
Cable inlet	1,2 m
Inlet voltage	230 V AC - 50 Hz
Lamp power supply voltage	230 V AC - 50 Hz
Lamp connection	E27
Max power	11 W
Lamp protection degree	IP65
Light bulb supplied	p/n 728001
Rewinding clutch	-
Lamp	p/n F230
Packing	No. 1 - 0,043 m3



OVERALL DIMENSIONS (mm)



Gross weight

6,8 ÷ 8,8 kg