



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 2215F

Cable reel s. 280, supply voltage 230 V single phase, without socket. Number of conductors 2, cable type 2 x 1,5 - H05 VV-F, cable length 15 + 1 (m). Rewinding clutch as standard.

AREAS OF USE

Aeronautics, Agriculture, Automotive, Cleaning, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Shipping and offshore, Railway transport

FEATURES

Information	230 V single phase
Protection degree of electrical part	IP44
Environment temperature	-5 ÷ +40 °C
Number of conductors	2
Cable type	2x1,5 - H05 VV-F
Cable length	15 + 1 m
Cable inlet	1,2 m
Max power use (20 °C) wound	1,1 kW
Max power use (20 °C) unwound	2,3 kW
Thermal protector	yes
Rewinding clutch	yes
Socket	-
Plug	-
Packing	No. 1 - 0,043 m ³
Gross weight	6,4 ÷ 8,2 kg



OVERALL DIMENSIONS (mm)



