



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 2315F

Cable reel s. 280, supply voltage 230 V single phase, without socket. Number of conductors 3, cable type 3G x 1,5 - H05 VV-F, cable length 14 + 1 (m). Rewinding clutch as standard.

AREAS OF USE

Aeronautics, Agriculture, Automotive, Cleaning, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Shipping and offshore, Railway transport

FEATURES

| | |
|--------------------------------------|------------------------------|
| Information | 230 V single phase |
| Protection degree of electrical part | IP44 |
| Environment temperature | -5 ÷ +40 °C |
| Number of conductors | 3 |
| Cable type | 3Gx1,5 - H05 VV-F |
| Cable length | 14 + 1 m |
| Cable inlet | 1,2 m |
| Max power use (20 °C) wound | 1,2 kW |
| Max power use (20 °C) unwound | 2,3 kW |
| Thermal protector | yes |
| Rewinding clutch | yes |
| Socket | - |
| Plug | - |
| Packing | No. 1 - 0,043 m ³ |
| Gross weight | 6,4 ÷ 8,2 kg |



OVERALL DIMENSIONS (mm)



