



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 2315T

Cable reel s. 280, supply voltage 230 V single phase, with 3 plugs and Schuko sockets IP44. Number of conductors 3, cable type 3G x 1,5 - H05 VV-F, cable length 14 + 1 (m).

AREAS OF USE

Aeronautics, Agriculture, Automotive, Cleaning, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Shipping and offshore, Railway transport

FEATURES

| | |
|--------------------------------------|--------------------|
| Information | 230 V single phase |
| Protection degree of electrical part | IP44 |
| Environment temperature | -5 ÷ +40 °C |
| Number of conductors | 3 |
| Cable type | 3Gx1,5 - H05 VV-F |
| Cable length | 14 + 1 m |
| Cable inlet | 1,2 m |
| Max power use (20 °C) wound | 1,2 kW |
| Max power use (20 °C) unwound | 2,3 kW |
| Thermal protector | yes |
| Rewinding clutch | - |
| Socket | Schuko plug |
| Plug | triple Schuko plug |
| Packing | No. 1 - 0,043 m3 |
| Gross weight | 6,4 ÷ 8,2 kg |



OVERALL DIMENSIONS (mm)



