



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 2325F

Cable reel s. 280, supply voltage 230 V single phase, without socket. Number of conductors 3, cable type 3G x 2,5 - H05 VV-F, cable length 9 + 1 (m). Rewinding clutch as standard.

AREAS OF USE

Aeronautics, Agriculture, Automotive, Cleaning, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Shipping and offshore, Railway transport

FEATURES

Information	230 V single phase
Protection degree of electrical part	IP44
Environment temperature	-5 ÷ +40 °C
Number of conductors	3
Cable type	3Gx2,5 - H05 VV-F
Cable length	9 + 1 m
Cable inlet	1,2 m
Max power use (20 °C) wound	1,9 kW
Max power use (20 °C) unwound	3,5 kW
Thermal protector	yes
Rewinding clutch	yes
Socket	-
Plug	-
Packing	No. 1 - 0,043 m3
Gross weight	6,4 ÷ 8,2 kg



OVERALL DIMENSIONS (mm)



