



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 3310F

Cable reel s. 280, supply voltage 230 V single phase, without socket. Number of conductors 3, cable type 3G x 1 - H07 RN-F, cable length 10 + 1 (m). Rewinding clutch as standard.

AREAS OF USE

Aeronautics, Agriculture, Automotive, Cleaning, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Shipping and offshore, Railway transport

FEATURES

| | |
|--------------------------------------|--------------------|
| Information | 230 V single phase |
| Protection degree of electrical part | IP44 |
| Environment temperature | -5 ÷ +40 °C |
| Number of conductors | 3 |
| Cable type | 3Gx1 - H07 RN-F |
| Cable length | 10 + 1 m |
| Cable inlet | 1,2 m |
| Max power use (20 °C) wound | 0,9 kW |
| Max power use (20 °C) unwound | 1,4 kW |
| Thermal protector | yes |
| Rewinding clutch | yes |
| Socket | - |
| Plug | - |
| Packing | No. 1 - 0,043 m3 |
| Gross weight | 6,4 ÷ 8,2 kg |



OVERALL DIMENSIONS (mm)



