



ADVANCED FLUID  
MANAGEMENT SOLUTIONS

**RAASM S.p.a.**

Via Marangoni 33, 36022  
S. Zeno di Cassola (VI) Italy  
Tel. +39 0424 570891  
info@raasm.com

## P/N 3315F

Cable reel s. 280, supply voltage 230 V single phase, without socket. Number of conductors 3, cable type 3G x 1,5 - H07 RN-F, cable length 9 + 1 (m). Rewinding clutch as standard.

### AREAS OF USE

Aeronautics, Agriculture, Automotive, Cleaning, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Shipping and offshore, Railway transport

### FEATURES

Information	230 V single phase
Protection degree of electrical part	IP44
Environment temperature	-5 ÷ +40 °C
Number of conductors	3
Cable type	3Gx1,5 - H07 RN-F
Cable length	9 + 1 m
Cable inlet	1,2 m
Max power use (20 °C) wound	1,2 kW
Max power use (20 °C) unwound	2,3 kW
Thermal protector	yes
Rewinding clutch	yes
Socket	-
Plug	-
Packing	No. 1 - 0,043 m3
Gross weight	6,4 ÷ 8,2 kg



### OVERALL DIMENSIONS (mm)



