



ADVANCED FLUID  
MANAGEMENT SOLUTIONS

**RAASM S.p.a.**

Via Marangoni 33, 36022  
S. Zeno di Cassola (VI) Italy  
Tel. +39 0424 570891  
info@raasm.com

## P/N 4410

Cable reel s. 280, supply voltage 400 V three phase.  
Number of conductors 4, cable type 4G x 1 - H05 VV-F,  
cable length 11 + 1 (m).

### AREAS OF USE

Aeronautics, Agriculture, Automotive, Cleaning,  
Building and road construction, Chemical industry,  
Manufacturing industry, Mining industry, Lube trucks  
and transports, Shipping and offshore, Railway  
transport

### FEATURES

Information	400 V three phase
Protection degree of electrical part	IP44
Environment temperature	-5 ÷ +40 °C
Number of conductors	4
Cable type	4Gx1 - H05 VV-F
Cable length	11 + 1 m
Cable inlet	1,2 m
Max power use (20 °C) wound	1,1 kW
Max power use (20 °C) unwound	2,3 kW
Thermal protector	yes
Rewinding clutch	-
Socket	-
Plug	-
Packing	No. 1 - 0,043 m <sup>3</sup>
Gross weight	6,4 ÷ 8,2 kg



### OVERALL DIMENSIONS (mm)

