



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 4510F

Cable reel s. 280, supply voltage 400 V three phase.
Number of conductors 5, cable type 5G x 1 - H05 VV-F,
cable length 11 + 1 (m). Rewinding clutch as standard.

AREAS OF USE

Aeronautics, Agriculture, Automotive, Cleaning,
Building and road construction, Chemical industry,
Manufacturing industry, Mining industry, Lube trucks
and transports, Shipping and offshore, Railway
transport

FEATURES

Information	400 V three phase
Protection degree of electrical part	IP44
Environment temperature	-5 ÷ +40 °C
Number of conductors	5
Cable type	5Gx1 - H05 VV-F
Cable length	11 + 1 m
Cable inlet	1,2 m
Max power use (20 °C) wound	1 kW
Max power use (20 °C) unwound	2,3 kW
Thermal protector	yes
Rewinding clutch	yes
Socket	-
Plug	-
Packing	No. 1 - 0,043 m3
Gross weight	6,4 ÷ 8,2 kg



OVERALL DIMENSIONS (mm)

