



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 2505745

Motor operated pump s. C25S for oil 230-400 V AC - 50 Hz - 275-480 V AC - 60 Hz 6 poles and 16 pumping elements, R 35:1, 70 litres reservoir and min level indicator

AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Centralized lubrication, Shipping and offshore, Railway transport

FEATURES

Flow rate	140 cm ³ /min
Tank capacity	70 l
Reducer ratio	35:1
Lubricant inlet connection	G 1/2" (f)
Lubricant outlet connection	G 1/4" (f)
N° of pistons	16
Working temperature	-25 ÷ +60 °C
Compatible fluids	oils > 40 cSt
Supply	230/400 V AC - 50 Hz - 275/480 V AC - 60 Hz
Protection degree	-
Velocity	6 poles: 870 ÷ 1100 rpm
Packing	No. 1 - 0,296 m ³
Net weight	40,3 kg
Gross weight	53,1 kg



OVERALL DIMENSIONS (mm)

