



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 1500020

Air operated pump s. C15F for grease with 10 liters reservoir (rechargeable), R 50:1 and air operated discharging valve

AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Centralized lubrication, Shipping and offshore, Railway transport

FEATURES

| | |
|-----------------------------|------------------------------|
| Flow rate | 1330 cm ³ /min |
| Tank capacity | 10 l |
| Pressure ratio | 50:1 |
| Air inlet connection | G 1/4" (f) |
| Lubricant outlet connection | G 3/8" (f) |
| Working temperature | -25 ÷ +60 °C |
| Lubricant | grease max NLGI 2 |
| Drum internal ø | 220 mm |
| Pump(R 50:1) | p/n 62541 |
| Drum cover | - |
| Membrane | p/n 10/617 |
| Packing | No. 1 - 0,056 m ³ |
| Net weight | 17,9 kg |
| Gross weight | 18,2 kg |



OVERALL DIMENSIONS (mm)

