



## P/N 33396

AISI 304 stainless steel transfer pump s. 600, with Viton® seals, for antifreeze and windshield washer, with AISI 304 stainless steel suction tube for drums 180÷220 kg

### AREAS OF USE

Aeronautics, Agriculture, Automotive, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Shipping and offshore, Railway transport

### FEATURES

|                               |   |
|-------------------------------|---|
| Flow rate                     | 30 l/min  |
| Ratio                         | 1:1   |
| Compatible fluids             | suitable for antifreeze and windshield washing liquid |
| Suction tube upper body       | AISI 304 stainless steel                              |
| Suction tube                  | AISI 304 stainless steel                              |
| Air inlet connection          | G 1/4" (f)  |
| Fluid outlet connection       | G 1/2" (f)  |
| Air working pressure          | 6 ÷ 8 bar   |
| Average air consumption       | 370 l/min   |
| Noise level                   | 81 dB   |
| max deliverable oil viscosity | SAE 50  |
| Bung adaptor                  | standard  |
| Suitable for drums or tanks   | suitable for drums 180 ÷ 220 kg                       |
| Packing                       | No. 1 - 0,02 m <sup>3</sup>                           |
| Weight                        | 7,4 kg  |



### OVERALL DIMENSIONS (mm)



