



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 33396

AISI 304 stainless steel transfer pump s. 600, with Viton® seals, for antifreeze and windshield washer, with AISI 304 stainless steel suction tube for drums 180÷220 kg

AREAS OF USE

Aeronautics, Agriculture, Automotive, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Shipping and offshore, Railway transport

FEATURES

Flow rate	30 l/min
Ratio	1:1
Compatible fluids	suitable for antifreeze and windshield washing liquid
Suction tube upper body	AISI 304 stainless steel
Suction tube	AISI 304 stainless steel
Air inlet connection	G 1/4" (f)
Fluid outlet connection	G 1/2" (f)
Air working pressure	6 ÷ 8 bar
Average air consumption	370 l/min
Noise level	81 dB
max deliverable oil viscosity	SAE 50
Bung adaptor	standard
Suitable for drums or tanks	suitable for drums 180 ÷ 220 kg
Packing	No. 1 - 0,02 m ³
Weight	7,4 kg



OVERALL DIMENSIONS (mm)



