



ADVANCED FLUID  
MANAGEMENT SOLUTIONS

**RAASM S.p.a.**

Via Marangoni 33, 36022  
S. Zeno di Cassola (VI) Italy  
Tel. +39 0424 570891  
info@raasm.com

## P/N 95D/61

AISI 304 stainless steel modular divorced pneumatic piston pump s. 900, R 6:1 - 42 l/min, with Teflon® seals

### AREAS OF USE

Aeronautics, Agriculture, Automotive, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Shipping and offshore, Railway transport

### FEATURES

Flow rate	42 l/min
Ratio	6:1
Compatible fluids	chemical and industrial fluids
Suction tube upper body	AISI 304 stainless steel
Suction tube	AISI 304 stainless steel
Air inlet connection	G 1/2" (f)
Fluid inlet connection	G 1" (f)
Fluid outlet connection	G 3/4" (f)
Max air consumption 8 bar	1,6 m <sup>3</sup> /min
Noise level	80 dB
Max supply pressure	8 bar
Suitable for drums or tanks	modular
Packing	1 - 0,045 m <sup>3</sup>
Weight	14,5 kg



### OVERALL DIMENSIONS (mm)

